

## SONIC-PRO<sup>®</sup> S6A Chemical Feed Flow Meter

THE S6A ACCURATELY MEASURES LIQUID CHEMICAL FEED from ranges of 10 – 5,000 mL/min and 100 -10,000 mL/min. This plug-and-play flow meter works right out of the box but is easily configurable via Blue-Central<sup>®</sup> desktop software.

Pre-calibrated chemicals include Water, Aqueous Ammonia 10%, Ammonium Hydroxide 30%, Ferric Chloride 40%, Sodium Hypochlorite 12.5%, Sodium Permanganate 40%, Hydrofluorosilicic Acid 25%, and Ammonium Sulfate 10%. Additional chemicals can be calibrated by performing a custom chemical calibration.

### Chemical Meter Model Number

S6A	S6A Chemical Feed Flow Meter				
<b>Flow Range</b>					
1	10 - 5000 mL/min (0.158 - 79.2 GPH)				
2	100 - 10,000 mL/min (1.58 - 158.5 GPH)				
<b>Display Options</b>					
1	Remote Mount Display				
2	Meter Mount Display				
<b>Elastometer Material (O-Ring)</b>					
V	TFE/P				
E	EP				
S6A	1	1	V	X	Sample Model Number

### Display Options



6 PUMPS & FILTRATION