

Pultruded Fiberglass Grating & Fiberglass Stair Tread Covers

DURAGRID® R-Bar Pultruded Grating

NOTES: ¹ 100 psf load, simple span (dimensions shown), 0.25" deflection.
² Weight per square foot is based upon cross rods 6" on center. Deduct 0.186 lbs/ft² for 12" on center.
 N/A : Not intended for pedestrian applications.
 For full load tables, visit <http://www.strongwell.com/gratingloadtables>

SERIES	ON CENTER SPACING	OPEN SPACE	# BARS PER FOOT OF WIDTH	% OPEN SPACE	BAR HEIGHT	SPAN ¹	WT/FT ²	FIGURE
R-6200	0.813"	0.500"	14.77	62%	1.00"	46	4.5	
R-7300	1.188"	0.875"	10.1	73%	1.00"	42	3.2	
R-8300	1.875"	1.563"	6.4	83%	1.00"	37	2.2	
R-9000	3.000"	2.688"	4	90%	1.00"	N/A	1.4	
R-9500	6.000"	5.688"	2	95%	1.00"	N/A	0.7	
R-9700	11.875"	11.563"	1	97%	1.00"	N/A	0.4	

Duratread™ Fiberglass Stair Tread Covers

DURATREAD™

MOLDED FIBERGLASS STAIR TREAD COVERS

STOCKING LEVELS MAY VARY. CALL FOR PRICING, COLOR OPTIONS AND AVAILABILITY.

RESINS OPTIONS:

GP — GENERAL POLYESTER RESIN SYSTEM VE — VINYL ESTER RESIN SYSTEM
 PP — PREMIUM POLYESTER RESIN SYSTEM FF — FOOD GRADE RESIN SYSTEM

Tread (inches)	Thickness 1/8" Weight (.lbs)	Thickness 1/4" Weight (.lbs)
8	16	31
9	18	34
10	19	37
11	21	40
12	23	44

*All covers are 12' long. • No minimum on black with yellow nose covers. • The minimum order quantity for all other colors is 5 pieces.

FRP - FIBER REINFORCED PLASTIC & GRATING

