

Drum Pump Kits & Accessories

Pump Kits



Finish Thompson offers engineered drum pump solutions based on specific classes of chemicals, container types and flow ranges. Kits include everything in one convenient carton. Includes drum pump tube, motor, discharge tubing, nozzle, wall bracket and additional accessories depending upon model. 40" (102cm) tube length is for 30/55 gallon drums; 48" (122cm) is for 275 gallon tote/IBC. Many other kit options available, contact Fabco.

Kits for Non-corrosive to Mildly Corrosive Liquids (cleaners, detergents, coolants and more)

Transfer Rate	Kit P/N	Tube Length	Motor Type
Medium, up to 17 gpm (64.4 lpm)	111615	40" (102cm)	2 speed, 115V/60 Hz, ODP
Medium, up to 15 gpm (56.8 lpm)	111620	40" (102cm)	Variable speed air motor
High, up to 40 gpm (151 lpm)	111639	40" (102cm)	Variable speed, 115V/60 Hz, ODP
High, up to 40 gpm (151 lpm)	111640	48" (122cm)	Variable speed, 115V/60 Hz, ODP
High, up to 22 gpm (83 lpm)	111643	40" (102cm)	Variable speed air motor
High, up to 22 gpm (83 lpm)	111644	48" (122cm)	Variable speed air motor


Kits for Corrosive Liquids (Acids, bases, plating solutions and more)

Transfer Rate	Kit P/N	Tube Length	Motor Type
High, up to 40 gpm (151 lpm)	111645	40" (102cm)	Variable speed, 115V/60 Hz, ODP
High, up to 40 gpm (151 lpm)	111646	48" (122cm)	Variable speed, 115V/60 Hz, ODP
High, up to 22 gpm (83 lpm)	111649	40" (102cm)	Variable speed air motor
High, up to 22 gpm (83 lpm)	111650	48" (122cm)	Variable speed air motor

Kits for Water Treatment Chemicals (Aluminum sulfate, HFSA, PAC, sodium hypochlorite and more)

Transfer Rate	Kit P/N	Tube Length	Motor Type
High, up to 37 gpm (140 lpm)	111666	40" (102cm)	Variable speed, 115V/60 Hz, TEFC
High, up to 37 gpm (140 lpm)	111667	48" (122cm)	Variable speed, 115V/60 Hz, TEFC
High, up to 31 gpm (117 lpm)	111670	40" (102cm)	Variable speed air motor
High, up to 31 gpm (117 lpm)	111671	48" (122cm)	Variable speed air motor

Kits for Flammable and Combustible Liquids (Acetone, MEK, lacquer thinner, naphtha and more)

Transfer Rate	Kit P/N	Tube Length	Motor Type
High, up to 40 gpm (151 lpm)	111657	40" (102cm)	Variable speed, Explosion proof, IP55, Class 1, Div. 1, Gr D, T4, 
High, up to 22 gpm (83 lpm)	111661	40" (102cm)	Variable speed air motor

Accessories

A wide variety of accessories are available including various specialized discharge hose to handle virtually any liquid, discharge nozzles for precise control of fluid flow, bung adapters to help keep pump/motor upright in the container, wall hangers for convenient storage when pump is not in use and flow meters to allow precise dispensing. Contact Fabco for more information.

Nozzle



Flow Meter



Air Motor Accessories



Wall Hangers



Bung Adapters



6 PUMPS & FILTRATION