

Snyder Vertical Tanks



Features:

- Industrial (ASTM D-1998-06) and Commercial design standards available.
- Available with cable restraint systems that meet 150 mph wind load and IBC seismic requirements.
- Specific gravity ratings are based on the industry's most severe calculation.
- Standard specific gravity choices are 1.5 and 1.9, other ratings are available upon request.
- All materials are UV stabilized for long-term outdoor service.

Material options:

- High-density linear polyethylene (HDLPE) - black and natural white color - Complies with FDA Regulation 177.1520 and NSF standard 61.
- Cross-linked, high-density polyethylene (XLPE) - black and natural white color.
- Opaque white sodium hypochlorite resin #880059 up to 12,500 gallons for outdoor application.
- Sulfuric acid HDLPE resin #880046 up to 15,000 gallons.

ALL DIMENSIONS AND US GALLON CAPACITIES ARE NOMINAL AND SUBJECT TO CHANGE

Note: FABCO recommends Flex Connectors for all lower outlets and inlets

PART NUMBER	US GALLONS	US BRIMFUL	DIAMETER (IN)	HEIGHT (IN)	MANWAY (IN)
1530000N	22	22	18"	23"	2"
1541000N	30	30	23"	23"	10"
1000110N	35	35	22"	36"	6"
1540700N	50	56	23"	38"	10"
5680000N	60	60	26"	40"	14"
1550000N	65	70	23"	46"	6"
1007200N	70	70	23"	42"	8"
1009000N	70	70	23"	41"	8"
5690100N	90	94	34"	41"	14"
1012700N	100	100	30"	41"	8"
8010000N	110	115	33"	41"	10"
5700100N	120	125	34"	51"	14"
1540200N	120	120	32"	39"	10"
1007300N	130	130	29"	51"	8"
1009500N	130	130	29"	49"	8"
1012800N	150	150	30"	59"	18"
5710100N	150	155	34"	61"	14"
1008400N	175	175	29"	66"	8"
1540400N	190	205	42"	47"	10"
1012900N	210	210	36"	55"	18"
1008000N	200	200	36"	53"	18"
5720100N	200	213	40"	57"	14"
1540000N	200	235	40"	48"	6"
1540300N	200	200	36"	59"	10"
8020000N	200	215	33"	69"	10"
1008100N	250	250	36"	64"	18"
5730100N	250	260	40"	69"	18"
5740100N	275	285	47"	59"	18"
1013000N	290	290	36"	72"	18"
1630000N	300	300	35"	80"	18"
1630200N	290	310	42"	59"	10"
1630100N	300	300	36"	82"	10"
8030000N	300	315	33"	94"	10"
1011200N	300	300	35"	85"	8"
8040000N	300	318	46"	51"	10"
5750100N	330	342	47"	68"	18"
1630300N	330	360	48"	55"	10"
1008200N	330	330	47"	50"	18"
1011600N	330	330	44"	58"	18"
5760100N	360	373	53"	59"	18"
1740000N	400	400	45"	62"	18"
5770100N	440	456	53"	69"	18"
5780100N	500	518	53"	77"	18"
1800000N	550	550	48"	75"	18"
1820000N	550	580	64"	47"	18"
8060000N	550	580	64"	46"	18"
1700200N	710	710	60"	68"	18"
1810000N	850	850	48"	117"	18"
1831000N	1000	1100	60"	89"	18"
1830000N	1100	1140	64"	90"	18"
1710000N	1100	1150	86"	55"	18"
8120000N	1100	1150	86"	55"	18"
1830200N	1200	1240	60"	109"	18"
1830400N	1300	1400	72"	87"	18"
1840300N	1400	1500	60"	128"	18"
1770000N	1500	1550	86"	72"	18"
8120100N	1500	1550	86"	72"	18"

continued..

Vertical Tanks



Note:

Snyder's integrally molded-in bottom drain fitting, SUMO, provides maximum drainage for vertical bulk storage tanks 2000 Gal. and larger and is available as an option in diameter sizes up to 6" depending on tank size.

Narrow Vertical Storage Tanks

Features:

- 18" manways for easy clean-out.
- Narrow 29" width designed to fit through 30" doorways.
- Fitting inset to protect against impact damage.
- Water applications only.



PART NUMBER	US GALLONS	US BRIMFUL	DIAMETER (IN)	HEIGHT (IN)	MANWAY (IN)
1840000N	1550	1600	64"	124"	18"
1780200N	1900	1930	72"	119"	18"
8300000N	1900	1950	64"	147"	18"
5050300N	2000	2000	96"	84"	18"
5050000N	2000	2300	90"	88"	18"
8130000N	2000	2100	90"	88"	18"
5090000N	2500	2600	90"	107"	18"
8140000N	2500	2600	90"	107"	18"
5090300N	2500	2600	96"	98"	18"
8390000N	2650	3000	102"	97"	18"
5130300N	3000	3000	96"	111"	18"
5130000N	3000	3150	90"	127"	18"
8160000N	3000	3150	90"	127"	18"
7410000N	3000	3200	102"	96"	18"
8190000N	3650	4000	102"	126"	18"
5190000N	3900	4100	90"	163"	18"
7421100N	4000	4300	120"	104"	18"
7360000N	4100	4200	102"	130"	18"
8200000N	4100	4400	120"	100"	18"
5210000N	4400	4600	90"	182"	18"
7420000N	4500	4700	102"	142"	18"
7000500N	4600	5100	120"	116"	18"
8210000N	4650	5000	102"	154"	18"
5480000N	4900	5100	90"	202"	18"
1002100N	5000	5100	102"	154"	18"
7020000N	5500	5600	90"	216"	18"
7000000N	5500	6000	120"	132"	18"
5250000N	5600	6350	142"	102"	18"
7430000N	6000	6300	102"	188"	18"
7140300N	6000	6500	120"	145"	18"
8220000N	6200	6300	120"	140"	18"
7140000N	6500	7000	120"	153"	18"
5300400N	6600	7100	120"	158"	18"
5330700N	7000	7700	142"	122"	18"
7440000N	7500	7800	102"	234"	18"
7370000N-	7900	8150	120"	177"	18"
5300600N	8000	8300	120"	186"	18"
7400000N	8500	8950	120"	194"	18"
5360100N	8750	9250	142"	146"	18"
7450000N	9500	9900	120"	215"	18"
5330000N	10,500	10,850	142"	169"	18"
5330300N	10,500	10,850	143"	177"	18"
5350000N	12,500	12,750	142"	198"	18"
3030100N	13,800	15,000	165"	184"	24"
5370000N	15,000	15,250	142"	234"	18"
5380000N	16,500	16,800	142"	257"	18"
3030000N	18,800	20,000	165"	242"	24"

NARROW VERTICAL STORAGE TANKS

PART NO.	LENGTH (IN)	WIDTH (IN)	HEIGHT (IN)	MANWAY (IN)	
44330S 300 NST	300	66	29	49	18
43856S 400 NST	400	66	29	70	18

ALL DIMENSIONS AND US GALLON CAPACITIES ARE NOMINAL AND SUBJECT TO CHANGE